

# MATERIAL SAFETY DATA SHEET

# SECTION 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

• Product name: DSC Gold Flush SB

• **Product Description:** Non-aqueous solvent system

• Manufacturer: Deep South Chemical, Inc.

229 Millstone Road

Broussard, LA 70518 (337) 837-9931

For Emergency: Call CHEMTREC 1-800-424-9300 Outside the U.S.A. (703)-527-3887

Contact Person: Glenn RayFormula: Proprietary

• MSDS Revised: January 1, 2014

#### SECTION 2. COMPOSITION/INFORMATION ON INGREDIENTS\_

			PEL(OSHA)		TLV(A	TLV(ACGIH)	
<b>Hazardous components</b>	<b>CAS Number</b>	%	TWA	STEL	TWA	STEL	IDLH
Proprietary Component		20-40	100ррі	n 150ppm	100ppm 150ppm	600ppm	
Acetate Ester	90438-79-2	40-60	N/E	N/E	N/E	N/E	N/E
Ethoxylated Alcohols	68130-47-2	2-5	N/E	N/E	N/E	N/E	N/E
Phosphate Ester	NA	4	N/E	N/E	N/E	N/E	N/E

Note: This product may contain trace amounts (<0.5ppm) of ethylene oxide CAS Number 75-21-8.

#### SECTION 3. HAZARDS IDENTIFICATION, INCLUDING EMERGENCY OVERVIEW

#### Effects of overexposure

**Inhalation:** This product may cause irritation to nose, throat, and respiratory tract

Skin Contact: This product may cause irritation to the skin. Defatting of the skin can occur with

frequent or long-term skin contact.

**Eve Contact:** Irritation to eyes.

**Ingestion:** There may be irritation of the mouth, throat, and digestive tract.

# **SECTION 4. FIRST AID MEASURES**

**Eyes:** Move victim away from exposure and into fresh air. If irritation persists, seek medical attention. For direct exposure, flush with clean water for 15 minutes. Hold eyelids apart to ensure flushing of the entire eye surface.

**Inhalation:** Move victim away from source of exposure and into fresh air. If irritation persists, seek medical attention. If victim is not breathing, artificial respiration should be administered.

**Skin:** Remove contaminated clothes. Cleanse affected area thoroughly with soap and water. If irritation persists, seek medical attention. Wash contaminated clothing.

**Ingestion:** Drink plenty water. Seek medical attention.

# SECTION 5. FIRE FIGHTING MEASURES\_

#### Fire fighting measures

Extinguishing Media: Use powder, foam, or CO<sub>2</sub>. Do not use water jet(may spread fire).

**Decomposition/Combustion Products:** Oxides of carbon.

**Special Fire Fighting Procedures:** Water spray to cool drums.

# **Explosive Properties:**

LEL: N/D UEL: N/D



## SECTION 6. ACCIDENTAL RELEASE MEASURES

Steps to be taken if material is released or spilled: Use proper personal protective equipment. Stay upwind and away from spill. Keep all sources of ignition and hot metal surfaces away from spill. If spill is indoors, ventilate area. Keep out of drains, sewers or waterways. Use sand or other inert material to contain and soak up spill.

**Waste disposal method:** Dispose of according to local, state and federal regulations in an approved disposal facility or recycling facility.

## **SECTION 7. HANDLING AND STORAGE**

**Storage:** Store in a well-ventilated area. Keep container tightly closed when not in use. Store in cool, dry area. Keep away from sources of ignition.

**Handling:** Use proper personal protective equipment. Avoid contact with skin or eyes. Avoid breathing of vapors. Handle in well-ventilated workspace. When handling do not eat, drink, or smoke.

**Other precautions:** Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat, flame, sparks or other sources of ignition.

# SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ventilation: Keep work area well ventilated.

Protective clothing: Impermeable gloves and impervious clothing as appropriate.

Eye protection: Chemical goggles where splashing may occur.

Respiratory Protection: Use appropriate respiratory protection when handling or in case of insufficient

ventilation.

**Special Protection: Safety** shower, eye bath, and washing facilities should be available.

# SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

**Specific gravity** @  $75^{\circ}F(H_2O = 1)$ : 0.89-0.92

Flash Point(PMCC Method)(°F): **144Vapor density (Air = 1):** N/D

**Solubility:** Oil soluble; dispersible in water. **Vapor pressure** @ **75:** approximately 0.8 mmHg

**Evaporation Rate:** N/D

**Appearance:** Pale yellow to colorless liquid.

**Odor:** Organic

**Boiling Point** (°F): 349-392 **Percent Volatile by Volume:** 100

**pH**: N/A

**Auto-ignition:** N/D

#### SECTION 10. STABILITY AND REACTIVITY

**Stability and Reactivity:** Stable in normal conditions. **Incompatible Materials:** Strong oxidizing agents.

Hazardous Decomposition Products: Smoke, carbon oxides.

Hazardous Polymerization: None described.

# SECTION 11. TOXICOLOGICAL INFORMATION

**Hazardous Ingredients:** Irritating to eyes and skin.

Immediate Health Effects: Irritation.

**Delayed Health Effects:** Defatting of skin with frequent or prolonged skin contact.

Acute Effects (Short term): -N/D Chronic Effects (Long term): -N/D



## SECTION 12. ECOLOGICAL INFORMATION

Persistence and Degradability: All the components are biodegradable.

Biodegradation: 42% (28 days),OECD 306

ErC50 (72 hours) Skeletonema costatum: N/D

LC50 (48 hours) Acartia tonsa: N/D

LC50 (10 days) Corophium voliotator: N/D

**Bioaccumulative Potential:** N/D

Aquatic Toxicity: 48 HR LC50 (mysid shrimp) N/D

#### **SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal:** If spilled, dispose according to local regulations. Recycle waste containers and clean out

residues.

#### SECTION 14. TRANSPORT INFORMATION

**DOT Transport Information:** 

Bulk (>119 gallons): NA 1993, Combustible Liquid N.O.S. (Contains D'Limonene), PG III

Non-Bulk: (< 119 gallons) DOT Non-regulated

#### SECTION 15. REGULATORY INFORMATION

**Toxic Substances Control Act (TCSA):** All ingredients are on the TSCA inventory or are not required to be listed on the TSCA inventory.

10

**CERCLA RQ-40 CFR 302.4(a)** 

Component CERCLA RQ (lbs)

Ethylene Oxide

SARA 302 Components-40 CFR 355 Appendix A

Component TPQ (Threshold Planning Quantity) (lbs)

Ethylene Oxide 1000

Section 311/312 Hazard Class-40 CFR 370.2

 $\boldsymbol{Immediate}\;(X)$ 

Delayed ()

Fire (X)

Reactive ()

Sudden Release of Pressure ( )

SARA 313-40 CFR 372.65

Component CAS Number %

None

#### SECTION 16. OTHER INFORMATION

**NFPA RATING:** Health (1) Fire (2) Reactivity (0)

The trace amounts of **ethylene oxide** (**EO**) in this product are not expected to result in either acute or long-term hazards when the material is handled in accordance with sections 7 & 8. You should be aware though, that EO is a cancer and reproductive hazard. Repeated exposure to ethylene oxide may be harmful. The Occupational Safety and Health Administration (OSHA) Permissible Exposure Level (PEL) for EO is 1ppm for an eight-hour time weighted average exposure. The ethylene oxide standard (29 CFR 1910.1047) regulates occupational exposure to EO from all sources, including products containing residual EO. It is the responsibility of the employer to comply with the OSHA ethylene oxide standard.

WE CANNOT ANTICIPATE ALL CONDITIONS UNDER WHICH THIS INFORMATION AND OUR PRODUCTS, OR THE PRODUCTS OF OTHER MANUFACTURERS IN COMBINATION WITH OUR PRODUCTS MAY BE USED. WE ACCEPT NO RESPONSIBILITY FOR RESULTS OBTAINED BY THE APPLICATION OF THIS INFORMATION OR THE SAFETY AND SUITABILITY OF OUR PRODUCTS, EITHER ALONE ON IN COMBINATION WITH OTHER PRODUCTS. USERS ARE ADVISED TO MAKE THEIR OWN TESTS TO DETERMINE THE SAFETY AND SUITABILITY OF EACH PRODUCT OR PRODUCT COMBINATION FOR THEIR OWN PURPOSES. UNLESS OTHERWISE OBTAINED IN WRITING, WE SELL THE PRODUCTS WITHOUT WARRANTY, AND BUYERS AND USERS ASSUME ALL RESPONSIBILITY AND LIABILITY FOR LOSS OR DAMAGE ARISING FROM HANDLING AND USE OF OUR PRODUCTS, WHETHER USED ALONE OR IN COMBINATION WITH OTHER PRODUCTS.



